



Specifications

Model	GS-3384 RT	
Measurements	US	Metric
Working height maximum*	39 ft	12.06 m
A Platform height maximum	33 ft	10.06 m
B Platform height - stowed**	5 ft 1 in	1.55 m
C Platform length:		
outside, extended - single deck	13 ft .5 in	3.98 m
outside, extended - dual deck	17 ft 6.25 in	5.34 m
D Slide-out platform extension deck - front	5 ft	1.52 m
E Slide-out platform extension deck - rear	4 ft	1.22 m
F Platform width - outside	6 ft	1.83 m
G Height - stowed:folding guardrails	8 ft 9.5 in	2.68 m
rails lowered	6 ft 6.75 in	2.0 m
H Length - stowed: single deck	12 ft 11.25 in	3.94 m
dual deck	13 ft 5 in	3.98 m
with outriggers	16 ft	4.88 m
I Width: standard tires	7 ft	2.13 m
high flotation tires	7 ft 11 in	2.41 m
A Wheelbase	9 ft 4 in	2.84 m
k Ground clearance - center	13 in	.33 m

Productivity

Maximum platform occupancy	7	7
Lift capacity	2,500 lbs	1,134 kg
Lift capacity - extension deck	500 lbs	227 kg
Drive speed - stowed	4.0 mph	6.4 km/h
Drive speed - raised	0.7 mph	1.1 km/h
Gradeability - stowed***	50%	
Maximum outrigger leveling: front to back	7°	
side to side	12°	
Turning radius - inside	10 ft 1.5 in	3.09 m
Turning radius - outside	19 ft 6 in	5.94 m
Raise/lower speed	45/29 sec	
Controls	proportional	
Drive	four wheel	
Tires - foam-filled rough terrain	10 x 31 in	25 x 79 cm

Power

Power source	Ford DSG-423 4 cylinder gas/LPG 75 hp (56 kW)
	Deutz D2011L03i 3 cylinder diesel 49 hp (36 kW) air cooled
Auxiliary Power unit	12 V DC
Fuel tank capacity	30 gal 113.6 L
Hydraulic system capacity	30 gal 113.6 L

Weight****

	12,005 lbs	5,445 kg
with outriggers	13,680 lbs	6,205 kg

Standards Compliance ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Based on RT tires. Deduct 2 in (5.8 cm) for turf and non-marking.

*** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.

**** Weight will vary depending on options and/or country standards.

Features

Standard Features

Measurements

- 39 ft (12.06 m) working height
- Up to 2,500 lbs (1,134 kg) lift capacity

Productivity

- 156.5 x 72 in (3.98 x 1.83 m) steel frame platform
- 60 in (1.52 m) extension deck
- Replaceable aluminum deck
- Folding guardrails
- Proportional lift and drive
- Onboard diagnostic system
- AC power to platform
- Full height swing gate
- Two self-closing gates
- 4WD
- Positive traction control
- Four-wheel braking
- Slide-out engine tray
- Foam-filled rough terrain tires (eco fill)
- Tilt level sensor with audible alarm
- Descent alarm
- Horn
- Hour meter

Power

- 75 hp (56 kW) Ford DSG-423 gas/LPG

Options & Accessories

Productivity Options

- Dual slide-out platform extension deck package 5 ft (1.52 m) front and 4 ft (1.22 m) rear
- Automatic leveling hydraulic outriggers
- Air line to platform
- Foam filled non-marking rough terrain tires 10 x 31 in (25 x 79 cm)
- High flotation air-filled tires 17 x 33 in (43 x 84 cm)
- High flotation foam-filled tires 16 x 33 in (41 x 84 cm)
- Dual flashing beacons
- Motion alarm
- Biodegradable hydraulic oil

Power Options

- 48 hp (36 kW) Deutz D2.9L4 diesel, Tier 4f
- AC, 2000 Watt generator (120 V / 60 Hz), (includes hydraulic oil cooler)
- Cold weather package
- Hydraulic oil cooler
- Diesel catalytic scrubber muffler
- LPG steel tank only, 33.5 lb capacity
- Welder ArcPro 275 heavy duty (includes hydraulic oil cooler)
- Welder ready package (includes hydraulic oil cooler)



Genie United States

18340 NE 76th Street
P.O. Box 97030
Redmond, Washington 98073-9730
Telephone +1 (425) 881-1800
Toll Free in USA/Canada +1 (800)-536-1800
Fax +1 (425) 883-3475

Distributed By: