



DIMENSIONS

- A. Overall operating height – dirt bucket 145.5" (3.69 m)
Height to*
- B. Bucket hinge pin 110.5" (2.81 m)
- C. Top of rollover protective structure (ROPS) 77" (1.96 m)
- D. Bottom of level bucket, loader arm fully raised 105" (2.67 m)
Overall length –
- E. w/o attachment 96.5" (2.45 m)
- F. w/bucket on ground 125" (3.18 m)
- G. Dump angle at maximum height –
Dirt bucket 42.5°
- H. Dump height – loader arm fully raised –
Dirt bucket 84" (2.13 m)
- J. Reach – loader arm fully raised –
Dirt bucket 22" (0.56 m)
Maximum attachment rollback –
- K. Bucket on ground 29°
- L. Bucket at full height 100°
- M. Wheelbase 37" (0.94 m)
- N. Ground clearance 6.5" (0.17 m)
- O. Angle of departure 26.5°
Clearance circle front –
- P. Less bucket 44" (1.12 m)
- Q. w/54" (1.37 m) dirt bucket on ground 73" (1.85 m)
- Q. w/63" (1.60 m) dirt bucket on ground 74.8" (1.90 m)
- R. Clearance circle rear 59" (1.50 m)
Operating weight 5,558 lb (2521 kg)

NOTE: *Dimensions taken with full fuel, 175 lb (80 kg) operator, and standard equipment including 100 lb (45 kg) counterweight, 54" (1372 mm) dirt bucket and 7.00 x 15 6PR tires.

PERFORMANCE SPECS

- Operating load 1,400 lb (635 kg)
- Tipping load 2,800 lb (1270 kg)
- Breakout force –
Lift cylinder 2,773 lbf
(12 335 N)
- Bucket cylinder 3,066 lbf
(13 638 N)
- Cycle time –
Raise 4.7 seconds
- Lower 2.6 seconds
- Dump 2.3 seconds
- Rollback 1.5 seconds

NOTE: SAE rated lift capacities. Cycle time measured with rated load in bucket.

Goodyear is a trademark of Goodyear Tire & Rubber Company.

Mitco is a trademark of Mitchell Industrial Tire Company.

Galaxy, Beefy Baby and Fat Foot are trademarks of the Galaxy Tire Co.

AirBoss and Altrakka are trademarks of IATCO Industries Inc.

© 1998 CASE CORPORATION
All Rights Reserved.

Case is a registered trademark of Case Corporation.

CASE CORPORATION
700 STATE STREET
RACINE, WI 53404 U.S.A.

CASE CANADA CORPORATION
450 SHERMAN AVENUE NORTH
HAMILTON, ON L8N 4C4 CANADA

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

Form No. CE 184-05-98
Replaces Form No. - None



IMPORTANT: Case Corporation reserves the right to change these specifications without notice and without incurring any obligation relating to such change. Case Corporation does not warrant the safety or reliability of attachments from other manufacturers.

Visit Case Corporation on the Web at:
<http://www.casecorp.com>
Printed in U.S.A.